# Jøtul F 100 ECO

**Jøtul F 100 ECO LL BP, cat. no. 30054475, Jøtul F 100 ECO LL SE BP, cat. no. 30054477**

**Jøtul F 100 ECO LL SE BBE, cat. no. 30054896, Jøtul F 100 ECO LL SE IVE, cat. no. 30054897 (LL=Long Legs 215mm, SE=Special Edidtion= Door without arches )**

**Jøtul F 100 ECO SL BP, cat. no. 30054476, Jøtul F 100 ECO SL SE BP, cat. no. 30054478 (SL=Short Legs 155mm, SE=Special Edidtion= Door without arches )**

*BP= Sort lakk/Black Paint, BBE= Blåsort Emalje/Blue Black Enamel, IVE= Edelhvit Emalje/ Ivory enamel UP= Ulakkert/Unpainted*

| Quantity | Pos. no. | Spareparts | Consist of pos.no: | Benevnelse | Description | Dim./Spec. |
|---|---|---|---|---|---|---|
| 1 | 1 | 12018369 | | Sideplate venstre BP | Side plate left BP | Cast iron min. 4mm thickness |
| 1 | 1 | 12018367 | | Sideplate venstre BBE | Side plate left BBE | Cast iron min. 4mm thickness |
| 1 | 1 | 12030896 | | Sideplate venstre IVE | Side plate left IVE | Cast iron min. 4mm thickness |
| 1 | 2 | | | Vermikulitt brennplate venstre | Vermiculite burn plate left | Vermiculite 600Kg/m³ |
| 1 | 3 | 12054617 | | Fyrbunn bakre UP | Inner bottom, rear UP | Cast iron min. 4mm thickness |
| 1 | 4 | 12054616 | | Fyrrist BP | Fire grate BP | Cast iron min. 4mm thickness |
| 1 | 5 | 12018340 | | Ventil opptenning UP | Valve ignition UP | Cast iron min. 4mm thickness |
| 1 | 6 | 12015042 | | Ben 215mm BP (for LL versjoner) | Leg 215mm BP (For LL versions) | Cast iron min. 4mm thickness |
| 1 | 6 | 12015034 | | Ben 215mm BBE (for LL versjoner) | Leg 215mm BBE (For LL versions) | Cast iron min. 4mm thickness |
| 1 | 6 | 12015035 | | Ben 215mm IVE (for LL versjoner) | Leg 215mm IVE (For LL versions) | Cast iron min. 4mm thickness |
| 4 | 6 | 51012223 | | Ben 215mm (4 stk) BP (for LL versjoner) | Leg 215mm (4 pcs) BP (For LL versions) | Cast iron min. 4mm thickness |
| 4 | 6 | 51012224 | | Ben 215mm (4 stk) BBE (for LL versjoner) | Leg 215mm (4 pcs) BBE (For LL versions) | Cast iron min. 4mm thickness |
| 4 | 6 | 51012227 | | Ben 215mm (4 stk) IVE (for LL versjoner) | Leg 215mm (4 pcs) IVE (For LL versions) | Cast iron min. 4mm thickness |
| 1 | 7 | 10024640 | | Skjermplate under | Heat shield under | Steel |
| 1 | 8 | 10024642 | | Askeskuff | Ash pan | Steel |
| 1 | 9 | 12054623 | | Bunnplate BP | Bottom plate BP | Cast iron min. 4mm thickness |
| 1 | 9 | 12054966 | | Bunnplate BBE | Bottom plate BBE | Cast iron min. 4mm thickness |
| 1 | 9 | 12054967 | | Bunnplate IVE | Bottom plate IVE | Cast iron min. 4mm thickness |
| 1 | 10 | 10024638 | | Ventilstang | Handle | ø6mm steel |
| 1 | 11 | 12021379 | | Askeleppe BP | Ash lip BP | Cast iron min. 4mm thickness |
| 1 | 11 | 12021380 | | Askeleppe BBE | Ash lip BBE | Cast iron min. 4mm thickness |
| 1 | 11 | 12021428 | | Askeleppe IVE | Ash lip IVE | Cast iron min. 4mm thickness |
| 1 | 12 | 12018374 | | Frontplate BP | Front plate BP | Cast iron min. 4mm thickness |
| 3 | 13 | 12020930 | | Glassklips | Glass clip | Steel & glass fibre gasket |
| 1 | 14 | 10024515 | | Stengejern | Latch bolt | Steel |
| 1 | 15 | 10023578 | | Skive M10 svart, spesial | Washer M10 Black, Special | Ø10,5xØ25x1,5 Steel |
| 1 | 16 | 10023475 | | Mutter sekskant M6 DIN 934 | Nut Hexagon M6 DIN 934 | St8.8 / ANSI B18.2 |
| 1 | 17 | 10024011 | | Fjær for klinke | Spring For Latch | Spring Steel |
| 1 | 18 | 12017311 | | Vrider (Klinke) svart lakkert | Latch, black painted | Cast iron min. 4mm thickness |
| 1 | 18 | 12020110 | | Vrider (Klinke) forniklet | Latch, nickel-plated | Cast iron min. 4mm thickness |
| 1 | 19 | 10023464 | | Skive | Washer | Ø6,4xØ12,5x1,6, St8,8, DIN 125, Steel |
| 1 | 20 | 10023919 | | Skive spesial | Washer special | Ø23xØ8,2x2 insulating mat. |
| 1 | 21 | 10024025 | | Treknott | Wooden knob | Hardved\hard wood |
| 1 | 22 | 10024023 | | Hylse | Sleeve | Ø8xØ6xL27,5mm, Steel |
| 1 | 23 | 10023611 | | Skrue, maskin panhode pozidrive | Screw, machine pan head pozidrive | M6x40, DIN 7985, Steel |
| 1 | 24 | 10023684 | | Skrue M6X25 lang tapp | Screw M6x25 Long Dog Point Set | Steel |
| 1 | 25 | 12021599 | 13,14,15,16,17,18,19,20,21,22,23,24,26,50,51,52,66 | Dør komplett - u/glass SE (Dør uten spiler BP) | Door , complete excl/glass SE (Door without arches BP) | BP |
| 1 | 25 | 12054959 | 13,14,15,16,17,18,19,20,21,22,23,24,26,50,51,52,66 | Dør komplett - u/glass SE (Dør uten spiler BBE) | Door , complete excl/glass SE (Door without arches BBE) | BBE |
| 1 | 25 | 12054962 | 13,14,15,16,17,18,19,20,21,22,23,24,26,50,51,52,66 | Dør komplett - u/glass SE (Dør uten spiler IVE) | Door , complete excl/glass SE (Door without arches IVE) | IVE |
| | 26 | | | Dør uten spiler SE BP | Door without arches SE BP | |
| 1 | 26 | | | Dør uten spiler SE BBE | Door without arches SE BBE | BBE |
| 1 | 26 | | | Dør uten spiler SE IVE | Door without arches SE IVE | IVE |
| 1 | 27 | 12021376 | 13,14,15,16,17,18,19,20,21,22,23,24,28,50,51,52,66 | Dør komplett - u/glass (Dør med spiler BP) | Door , complete excl/glass (Door with arches BP) | BP |
| 1 | 28 | | | Dør med spiler BP | Door without arches BP | |
| 1 | 29 | 10024654 | | Glass | Glass | 379x270x4mm, keramisk\ceramic |
| 2 | 30 | 10024103 | | Hengseldubb, sortkromatisert | Hinge pin, black chromated | Ø6x33mm, Steel |
| 2 | 30 | 10023975 | | Hengseldubb, forniklet | Hinge pin, nickel plated | Ø6x33mm |
| 1 | 31 | 10054451 | 2,32 | Brennplater sett V+H | Burn plates kit L+R | Vermiculite 600Kg/m³ |
| 1 | 32 | | | Vermikulitt brennplate høyre | Vermiculite burn plate right | Vermiculite 600Kg/m³ |
| 1 | 33 | 12018364 | | Sideplate høyre BP | Side plate right BP | Cast iron min. 4mm thickness |
| 1 | 33 | 12018362 | | Sideplate høyre BBE | Side plate right BBE | Cast iron min. 4mm thickness |
| 1 | 33 | 12030893 | | Sideplate høyre IVE | Side plate right IVE | Cast iron min. 4mm thickness |
| | 34 | 10024413 | | Hylse | Sleeve | Ø10xØ6,2xL10mm, Steel |
| 1 | 35 | 12054620 | | Luftbrem BP | Air deflector BP | Cast iron min. 4mm thickness |
| | 36 | 12018338 | | Ventilplate UP | Valve plate UP | Cast iron min. 4mm thickness |
| | 37 | 12017438 | | Ventilsleide BP | Valve BP | Cast iron min. 4mm thickness |
| 1 | 38 | 10054452 | | Luftbegrenser | Air restrictor | Steel |
| 1 | 39 | 12021582 | 39,44,55,61(2pcs) | Topplate komplett BP | Top plate complete BP | Cast iron min. 4mm thickness |
| 1 | 39 | 12021583 | 39,44,55,61(2pcs) | Topplate komplett BP | Top plate complete BP | Cast iron min. 4mm thickness |
| 1 | 39 | 12033806 | 39,44,55,61(2pcs) | Topplate komplett BP | Top plate complete BP | Cast iron min. 4mm thickness |
| 1 | 40 | 12018816 | | Røykstuss innvendig Ø125 BP | Smoke outlet, dripless Ø125 BP | Cast iron min. 4mm thickness |
| 1 | 40 | 12018813 | | Røykstuss innvendig Ø125 BBE | Smoke outlet, dripless Ø125 BBE | Cast iron min. 4mm thickness |
| 1 | 40 | 12049995 | | Røykstuss innvendig Ø125 IVE | Smoke outlet, dripless Ø125 IVE | Cast iron min. 4mm thickness |
| 1 | 41 | 12054621 | | Ledeplate UP | Exhaust deflector UP | Cast iron min. 4mm thickness |
| 1 | 42 | 12018331 | | Hvelv UP | Baffle UP | Cast iron min. 4mm thickness |
| 1 | 43 | 12031154 | | Bakplate BP | Rear plate BP | Cast iron min. 4mm thickness |
| 1 | 44 | 12018811 | | Røykhullsdeksel BP | Smoke outlet cover BP | Cast iron min. 4mm thickness |
| 1 | 44 | 12018807 | | Røykhullsdeksel BBE | Smoke outlet cover BBE | Cast iron min. 4mm thickness |
| 1 | 44 | 12018808 | | Røykhullsdeksel IVE | Smoke outlet cover IVE | Cast iron min. 4mm thickness |
| 2 | 45 | 12018394 | | Deksel sekundærluft UP | Cover for air manifold UP | Cast iron min. 4mm thickness |
| 1 | 46 | 10024639 | | Skjermplate bak, svart | Heat shield rear, black | Steel |
| 1 | 46 | 10050009 | | Skjermplate bak, ubeh alu zn | Heat shield rear, untreated alu zn | 0,9mm Alu zn belagt stål\coated steel |
| 4 | 47 | 12015095 | | Ben 155mm BP (for SL versjoner) | Leg 155mm BP (For SL versions) | Cast iron min. 4mm thickness |
| 4 | 47 | 12015093 | | Ben 155mm BBE (for SL versjoner) | Leg 155mm BBE (For SL versions) | Cast iron min. 4mm thickness |
| 4 | 47 | 12028848 | | Ben 155mm IVE (for SL versjoner) | Leg 155mm IVE (For SL versions) | Cast iron min. 4mm thickness |
| 1 | 47 | 51012177 | | Ben 155mm (4 stk) BP (for SL versjoner) | Leg 155mm (4 pcs) BP (For SL versions) | Cast iron min. 4mm thickness |
| 1 | 47 | 51012178 | | Ben 155mm (4 stk) BBE (for SL versjoner) | Leg 155mm (4 pcs) BBE (For SL versions) | Cast iron min. 4mm thickness |
| 1 | 47 | 51012179 | | Ben 155mm (4 stk) IVE (for SL versjoner) | Leg 155mm (4 pcs) IVE (For SL versions) | Cast iron min. 4mm thickness |
| 1 | 48 | 10026011 | | Lest håndtak flatt | Loose handle flat | 2mm steel |
| 4 | 49 | | 50027204 (5m) | Pakning (til bakplate) | Gasket (for rear plate) | V-125x30 mm graph W/A (4pcs) |
| 2 | 50 | | 50027204 (5m) | Pakning under glass | Gasket under glass | V-125x15 mm graph W/A (2pcs) |
| 1 | 51 | | 50027205 (5m) | Pakning til glass | Gasket for glass | LD-250-2 graph Ø6,4x1300mm |
| 1 | 52 | | 50027203 (5m) | Pakning mellom dør og front | Gasket Between door and front | LD 375-2 Ø9,5x1620mm |
| 1 | 53 | | 50027205 (5m) | Pakning underside av ventilplate | Gasket for valve plate | LD-250-2 graph Ø6,4x835mm |
| 1 | 54 | | 50027201 (5m) | Pakning mellom røykstuss og røykrør | Gasket between smoke outlet and flue | LD-187 graph Ø4,8x500mm |
| 1 | 55 | | 50027203 (5m) | Pakning for topp-plate | Gasket for top plate | LD 375-2 Ø9,5x1620mm |
| 2 | 56 | | 50027205 (5m) | Pakning mellom bakplate og deksel sekundærluft | Gasket between rear plate and cover for air manifold | LD-250-2 graph Ø6,4x750mm (2pcs) |
| 3 | 57 | 10023780 | | Skive M6 Ø6,4xØ18x1,6 DIN 9021 | Washer M6 Ø6,4xØ18x1.6 DIN 9021 | St8.8 / ANSI B18.2 |
| 4 | 58 | 10023559 | | Skive M8 Ø8,4xØ20x1.5 DIN 522 | Washer M8 Ø8,4xØ20x1.5 DIN 522 | St8.8 / ANSI B18.2 |
| 1 | 59 | 10024339 | | Skive Ø6.2x12x1.8 Messing | Washer Ø6.2x12x1.8 Brass | Brass |
| 1 | 60 | 10023576 | | Skrue Gjengestift med Hul ende M6x25 DIN 916 | Screw Socket Set with Cup point M6x25 S DIN 916 | Steel, black |
| 6 | 61 | 10023545 | | Skrue sekskant med flens M6x12 DIN 6921 | Screw Hex Cap Flange M6x12 DIN 6921 | St8.8 / ANSI B18.2 |
| 15 | 62 | 10023541 | | Skrue sekskant med flens M6x16 DIN 6921 | Screw Hex Cap Flange M6x16 DIN 6921 | St8.8 / ANSI B18.2 |
| 2 | 63 | 10023540 | | Skrue sekskant med flens M6x20 DIN 6921 | Screw Hex Cap Flange M6x20 DIN 6921 | St8.8 / ANSI B18.2 |
| 4 | 64 | 10023536 | | Skrue sekskant med flens M6x25 DIN 6921 | Screw Hex Cap Flange M6x25 DIN 6921 | St8.8 / ANSI B18.2 |
| 3 | 65 | 10023574 | | Skrue sekskant med flens M6x40 DIN 6921 | Screw Hex Cap Flange M6x40 DIN 6921 | St8.8 / ANSI B18.2 |
| 3 | 66 | 10023561 | | Skrue sylinderh. innv. sekskant lavh. M6x8 DIN 7984 | Screw cylinder head int.hex. low head M6x16 DIN 7984 | St8.8 / ANSI B18.2 ,black |
| 2 | 67 | 10048871 | | Skrue sekskant M6x16 selvgjengende DIN 7500D | Screw hex cap M6x16 selfthread DIN 7500D | Steel, ELZn |
| 3 | 68 | 10023666 | | Mutter sekskant med flens M6 DIN 6923 | Nut Hexagon Cap Flange M6 DIN 6923 | St8.8 / ANSI B18.2 |
| 3 | 69 | 10023998 | | Hylse | Sleeve | Ø10xØ6,2xL15mm, Steel |
| 1 | | | | | | |
| | | | **Smoke Outlet For UK, Ø125mm dripless** | | | |
| 1 | 70 | 51012033 | 70,61(2pcs),62(2pcs) | Røykstuss innvendig Ø125 BP (for UK) | Smoke outlet, dripless Ø125 BP (for UK) | Cast iron min. 4mm thickness |
| 1 | 70 | 51012034 | 70,61(2pcs),62(2pcs) | Røykstuss innvendig Ø125 BBE (for UK) | Smoke outlet, dripless Ø125 BBE (for UK) | Cast iron min. 4mm thickness |
| | | | | | | |
| | | | **Smoke Outlet, Ø150mm dripless** | | | |
| 1 | 71 | 12021463 | | Røykstuss innvendig Ø150 BP | Smoke outlet, dripless Ø150 BP | Cast iron min. 4mm thickness |
| | | | | | | |
| | | | **Smoke Outlet, Ø125mm non dripless** | | | |
| 1 | 72 | 12018329 | | Røykstussutvendig Ø125 BP | Smoke Outlet, Ø125mm non dripless BP | Cast iron min. 4mm thickness |
| 1 | 72 | 12018328 | | Røykstussutvendig Ø125 BBE | Smoke Outlet, Ø125mm non dripless BBE | Cast iron min. 4mm thickness |
| | | | | | | |
| | | | **Heatshield Rear , extra complete** | | | |
| 1 | 73 | 50012956 | | Skjermplate bak, ekstra komplett BP | Heatshield Rear , extra complete BP | Steel |
| | | | | | | |
| | | | **Floor Plates Cast Iron for Norway** | | | |
| | 74 | 51012191 | 75, 76 | Gulvplater støpejern Norge BBE | Floor Plates Cast Iron Norway BBE | Cast iron min. 4mm thickness width 630, depth 766, height 17 |
| | 75 | | | Gulvplate under støpejern BBE | Floor Plate Under Cast Iron BBE | Cast iron min. 4mm thickness width 630, depth 467, height 17 |
| | 76 | | | Gulvplate foran støpejern BBE | Floor Plate Front Cast Iron BBE | Cast iron min. 4mm thickness width 630, depth 317, height 17 |
| | | | | | | |
| | | | | | | |
| 1 | 77 | 12021378 | 16,19,20,21,22,23,60,54 | Treknott og smådeler | Wooden knob and small parts | |
| | | | | | | |
| 1 | 77 | 12021450 | 14,15,16,17,18,19,20,21,22,23,24 | Vrider kompl (frontdør) Sort | Latch compl (front door) Black | |
| 1 | 77 | 12021451 | 14,15,16,17,18,19,20,21,22,23,24 | Vrider kompl (frontdør) Forniklet | Latch compl (front door) Nickel crom | |
| | | | | | | *Draw. no. 900290-P00* |