

DECLARATION OF PERFORMANCE (DOP)

| NO. 95003600 CPR-20170622 | |
|---|---|
| 1. Product Type: | Insert fired by solid fuel |
| 2. Type, batch or serial number: | Scan 5003 FR/FL |
| 3. Intended use of the product: | Heat distribution/room heating Without hot water supply Fuel type: Wood |
| 4. Name and Address of the manufacturer: | For: Scan A/S · Glasvænget 3-9 · DK-5492 Vissenbjerg By: ROMOTOP spol. s r.o. · Komenského 325 · CR-742 01 Suchdol nad Odrou Company ID No.: 47678186 |
| 5. Contact address: | Scan A/S · Glasvænget 3-9 · DK-5492 Vissenbjerg |
| 6. AVCP System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V | System 3 |
| 7. Notified body: Test report no: | SZU NB-No 1015 30-12869-T-1 |
| 8. Declared performance | |
| Harmonized technical specification | EN 13229:2001/A2:2004 |
| Essential characteristics | Performance |
| Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out | A1 Minimum distances in mm: Rear = 400 Sides = 400 Front = 800 NPD |
| Emission of combustion products | CO [940 mg/Nm ³] NOx [118 mg/Nm ³] OGC [53 mg/Nm ³] Dust [11 mg/Nm ³] |
| Surface temperature | Pass |
| Electrical safety | - |
| Cleanability | Pass |
| Maximum water operating pressure | - |
| Flue gas temperature at nominal heat output [EN] | T [206°C] |
| Mechanical resistance (to carry a chimney/flue) | NPD |
| Thermal output Normal heat output Room heating output Water heating output | 5,7 kW - - |
| Energy efficiency | η [85,7 %] |

DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Brian Steen Ørum, Senior Project Manager)

Vissenbjerg, 22. juni 2017

(Place and date of issue)

SCAN


(Signature)