Model identifier(s): Scar	183								
Indirect heating functionality				No					
Direct heat output(kW)				5					
Indirect heat output(kW)				N.A					
					Emissions from space heating at nominal heat output				
			Preferred fuel	Model		OGC	СО	NO _x	
Fuel					identifier(s)	[X] mg/Nr	n ₃ (13 %	0,)	^
Wood logs with moisture content ← 25%				Yes	No	23	87	1017	98
Compressed wood with moisture content < 12%				No	No				
Other woody biomass				No	No				
Anthracite and dry steam coal				No	No				
Hard coke				No	No				
Low temperature coke				No	No				
Bituminous coal				No	No				
Lignite briquettes				No	No				
Peat briquettes				No	No				
Blended fossil fuel briquettes				No	No				
Other fossil fuel				No	No				
Blended biomass and fossil fuel briquettes				No	No				
Other blend of biomass and solid fuel				No	No				
Characteristics when op	erating with	the prefer	red fuel						
Seasonal space heating energy efficiency η_c [%]									
Energy Efficiency Class	- Cr	, 151 1		A+					
Energy Efficiency Index (E	108								
Item	Symbol	Value	Unit	lt lt	Symbol	Symbol Value		Unit	
Heat output	Зутьот	Value	Onte	Use efficiency (NCV as re				de	Onte
Nominal heat output	P_{nom}	5	kW	Useful efficiency at nominal heat output		η _{th, nom}	0.1		%
Minimum heat output (indicative)	P_{min}	N.A.	kW	Useful efficiency at minimum heat output (indicative)		η _{th, min}	η _{th, min} N.A.		%
Auxiliary electricity consumption Type of heat output/room temperature control (selec									alast ana)
, i				single stage				etect one)	
At nominal heat output	el _{max}	X,XXX	kW	temperatur	lyes		/no]		
At minimum heat output	el _{min}	X,XXX	kW	two or more	l lyes/		/no]	Yes	
In standby mode	el _{sB}	x,xxx	kW	with mecha temperatur	t room [yes		/no]		
				with electro control	perature [yes/no]		/no]		
				with electro	perature [yes/no]		/no]		
				with electro	perature	[yes/no]			
				Other cont	- nultiple_se <u>le</u>	ections po	ossible)		
				room tempe presence de	l, with	[yes,	/no]		
				room tempe open windo	, with [yes/no]		/no]		
			with distance control option			[yes,	/no]		
Permanent pilot flame p									
Pilot flame power requirement (if applicable)	P_{pilot}	N.A.	kW			/	1		
Contact details	Name and address of the supplier: Brian Ørum, R&D Manager, Scan A/S, Denmark								